

# Secure Your Critical Projects

Ensure excellent system reliability and easy maintenance for large applications.

Linux Platform & **RAID Function** 

Up to 128CH **Full HD Cameras** 

SAS JBOD for Local Expansion

Surveon Enterprise VMS



## Surveon NVR7300 Series

NVR7312/NVR7316 - 128-ch Mission Critical Storage NVR

#### **Features**

- Support up to 128CH 5MP (or above) cameras without frame drop, total recording throughput - 768Mbps
- Built-in SAS JBODs and iSCSI for storage expansion
- Support 14x 3U 16-bay JBOD (total 240HDDs) or 5x 4U 60-bay JBOD (total 316HDDs)
- Server-storage design for best cost-performance ratio
- Cableless design with hot swappable redundant components for easy maintenance
- Built-in H/W RAID function for data protection
- Intuitive set-up page for hassle-free installation

#### Surveon Proven End to End Solutions

Surveon Linux-based RAID NVR7300 Series, adding another powerful option to the existing Corporate series product line. Supporting up to 128CH 1080P full HD cameras with non-stop recording and 12 or 16-bay hot-swappable HDDs, NVR7300 Series is an ideal surveillance solution for performancedriven applications such as airport and train station.









## **3rd Party Camera Supported:**

























## **Surveon NVR7300 Series**

## NVR7312/NVR7316 - 128-ch Mission Critical Storage NVR


### **Technical Specifications**

Model		NVR7312A1	NVR7316A1
System	Main Processor	Intel® Xeon E3 Quad Core 3.2GHz	
	Operating System	Linux	
Storage	Internal HDD	12	16
	RAID	RAID 1, 5, 6, 1+Spare, 5+Spare, 6+Spare	
	SAS Expansion	1x 6G SAS Expansion Port	
Video	IP Camera Input	32 / 48 / 64 / 96 / 128	
	Output	2x HDMI, 1x VGA	
Alarm	Input/Output	8/2	
Display	Resolution	1920 x 1080, 1280x1024, 1280x720, 1024x768	
	Display Split	1/4/5/7/9/10/16/32	
Recording	Resolution	5M / 3M / 1080P / 720P / D1	
	Record Rate	1920 fps @ 1080P	
	Bit Rate	768 Mbps	
	Record Mode	Always, Motion, Event	
Video Detection & Alarm	Video Intelligence	10 Advanced Video Analytics Engines	
Playback & Backup	Playback Channel	16	
	Search Mode	Date / Time, Event, VI	
Network	Ethernet	2 x RJ-45 Port (100/1000)	
General	Power Supply	Input Voltage: 100V~240V	
	Power	Dual Redundant PSU (460)W	
	Working Environment	Humidity: $5\%$ to $80\%$ (non-condensing) Temperature: $5C^\circ$ to $35^\circ$ C	
	Dimension	2U 19-inch rackmount with chassis ears: (H)88.00mm x (W)447.40mm x (L)524.41mm	3U 19-inch rackmount with chassis ears: (H)130.00mm x (W)447.40mm x (L)524.20mm
	Weight	13.60kg/ 29.98lbs (without HDDs)	21.54kg/ 47.49lbs (without HDDs)

### **Surveon NVR7300 Series Feature Highlights**

Storage Expandability

Support 14x JBOD 3U 16-bay (total 240HDDs) or 5x JBOD 4U 60-bay (total 316HDDs) two options.



Swappable Modules

Low maintenance modular design to prevent accidental disconnections or loose cables.



#### Multi-functional Combination

The Server + Storage design provides high integration with other devices for system stability.



#### Smooth Performance

Patented read/ write technology to guarantee performance during drive IO delay.







Surveon Headquarters

10F-3, No.102, Sec. 3, Jhongshan Rd., Jhonghe Dist., New Taipei City 235, Taiwan Tel: +886-2-2226-2966 Fax: +886-2-2226-8278 Marcom: marketing@surveon.com Technical support: support@surveon.com

Surveon Corporation 435 Lakeside Dr. Sunnyvale, CA 94085, U.S.A. Tel: +1-408-988-5728 Fax: +1-408-435-5048 E-mail: sales.us@surveon.com Technical support: support.us@surveon.com

Europe (EMEA) Surveon Europe Limited 5 Ringway Centre, Edison Road, Basingstoke, Hampshire, RG21 6YH, UK Tel: +44 (0) 1256 844 566 E-mail: sales.europe@surveon.com Technical support: support.europe@surveon.com Surveon Technology Inc. Room 402-403, Tower D, Yuanyang International Center, East Fourth Ring Central Road, Chaoyang District, Beijing, China, 100025 Tel: +86-10-6310-6168 E-mail: sales.china@surveon.com Technical support: support.china@surveon.com