NVR500

8 Channel Megapixel NVR



- 8 Channel Megapixel Video Recording
- E-Map Monitoring and Management
- Real Time Video Analytics
- · Active Alarm and Event Handling
- Powerful Investigative Modes
- Industrial Grade Platform
- 3 Year Warranty

VMS Specifications

Live View	Real-time network camera discovery Versatile views of various screen divisions HTML and image overlays Multiple views supported View patrolling for single or multiple views Real time vidoe/event alarm display Instant playback Video clip bookmarking
eMAP	 Drag-n-drop camera manipulation Directional camera display Hierarchical map structure Real time event alert Instant live video of camera Multiple maps supported
PTZ	Pan, tilt, zoom operations (dependent of camera) Built-in, floating PTZ control panel Preset position (dependent of camera) Scheduled or continous camera patrolling Event-driven camera patrolling
Investigation	Search by date, time, camera Search by pre-defined recent time Search by VI event combinations Search over multiple days Search over multiple cameras Video clip bookmarking and commenting Search via built-in VI analyzer Customizable bookmark Intuitive, video thumbnail search results Cue-in, cue-out and repeat Quick playback by video thumbnail 1/8, 1/4, 1/2, 1x, 2x, 4x, 8x play, pause, stop AVI-formated video clip export 4-channel synchronized playback*
Instant Playback	 Supported in video alarm, event alarm, view functions Pre-defined playback durations Video clip bookmarking
Video Intelligence	 General motion detection Missing object detection Foreign object detection Intrusion detection Forbidden area detection Tampering detection Virtual fence* Object counting*

Recording Policy	Continuous recording Manual recording Scheduled recording on daily or weekday basis Event-driven recording along with rules Pre-alarm recording up to 45 minutes Post alarm recording up to 45 minutes
Rule Manager	Conditional recording/alert/notification Email, FTP, SMS, phone notifications Sound, alarm, round-the-clock alerts
Remote Management	Full functional operation & management via standalone VMS Client
3rd Party IPCAM	ACTI, AXIS, SONY, VIVOTEK, Arecont Vision, HIKVISION, IQinVision, MOBOTIX, Panasonic, Asoni, AVTECH, D-Link, SAMSUNG
General & Misc	Video codec: H.264, MPEG4, MJPEG Image enhancement Video privacy mask Digital zoom in, zoom out Log viewer Windows lockup Client auto login Digital I/O management Automatic storage recycling Client-server architecture Guaranteed performance of long period recording Configurable video retention period Digital watermark proofing* Language supported: English, French, German, Portuguese, Spanish, Simple Chinese, Traditional Chinese

^{*} Available in VMS 2.4.5




All specifications are subject to change without notice.
 All brand names and registered trademarks are the property of their respective owners.

Network Video Recorder

NVR500


Part Names and Functions

Front View



LED Indicators

Rear View



- Mouse
- 2 Keyboard
- 3 Serial
- 4 VGA
- 4 x USB
- Audio In/out
- Voltage Selector
- 8 Ethernet
- Power Switch
- Power Socket
- Power Supply

Package Content

Contents	Quantity
NVR500 Network Video Recorder	1
NVR Recovery DVD	1
Power Cord	1
Quick Installation Guide	1
HDD Sledge	1
HDD	max.3

Ordering Information

Part Number	Description
NVR0500-10B16A	8 Channel NVR, 3x1TB SATA HDD
NVR0500-10B16B	8 Channel NVR, 2x1TB SATA HDD
NVR0500-10B16C	8 Channel NVR, 1x1TB SATA HDD

Hardware Specifications

Network Video Recorder		
System	Up to 8 MEGA network cameras	
Storage	HDD capacity: SATAx3	
Server Processor	Intel® CPU @2.0GHz	
System Memory	2GB, DDR2	
I/O Interface	RJ-45: 1xGigabit Ethernet VGA:1xD-Sub Audio: 1xLine-in, 1xLine-out USB: 2xUSB 2.0 RS232x1 PS2x2	
Electrical	Input voltage: 115 V AC @ 6 A/240 V AC @ 3 A Frequency: 47 to 63 Hz Power: Single 250 watt	
Environment	Temperature: • Operating: 10 °C to 35°C (50 °F to 95 °F) • Non-operating: -40 °C to 70°C (-40 °F to 158 °F) Humidity: • Operating: 5 % to 95 %, non-condensing • Non-operating: 5 % to 95 % non-condensing	
Dimensions	40.42 x 34.02 x 9.71 cm (15.91"x 13.39"x 3.82")	
Gross Weight	Gross Weight: 11.36 kg (26 lb)	
Certifications	FCC Class B, CE, CB, UL60959/IEC 60950,BSMI, CCC	

