GSe Pro 1004 Serise

Cloud NVR Series



- Maximum 4/9/16CH Megapixel Recording (up to 5MP or above)
- Support 4-bay Hot-Swappable SATA Hard Disk
- Enterprise Hardware RAID Function for Data Protection
- Built-in Surveon Enterprise VMS
- Scalable Client-Server Architecture


Software Specifications


Joinnaid	specifications.		
• Ve • Mu • Vie • Re • Su fis	Real-time network camera discovery Versatile views of various screen divisions Multiple views supported View patrolling for single or multiple views Real time video/event alarm monitoring Support 3 installation modes and 5 different	Rule Manager Remote	• Conditi • Email, F Panel, R • Sound, • Suppor • Remote
	fisheye dewarp display modes • Support live audio	Management	• Remote
eMAP	Drag-n-drop camera manipulation Hierarchical and multiple layer map structure Real time event alert Instant live video of camera	Remote Client 3rd Party IPCAM	Web Cli ACTi, Al Hikvision
PTZ	Pan, tilt, and zoom operations (depends on camera) Built-in PTZ control panel Preset position (depends on camera) Event-driven camera patrolling Support OnScreen PTZ	Storage Expansion General & Misc.	Built-inVideo pDigital zLog viewClient a
1/0	Digital I/O management Support Ethernet Digital I/O Controller		• Automa
Multiple Displays	Support dual monitors Supports live view, playback, eMap functions (depends on product) Direct display to secondary monitor(s)		Custom Digital v Suppor Suppor Suppor Auto po Suppor Suppor Suppor Suppor Suppor Suppor Suppor Suppor Suppor Suppor
Investigation	Search by date, time, and camera Search over multiple days Search over multiple cameras Different colored recording indicator on calendar Intuitive, video thumbnail search results Cue-in, cue-out and loop playback Quick playback by video thumbnails		
	 1/8, 1/4, 1/2, 1x, 2x, 4x, 8x play, pause, stop AVI-formatted video clip export Up to 16 channel synchronized playback (depends on product) Support 3 installation modes and 5 different fisheye dewarp playback display modes 	Language	Support Czech, D Korean, I Spanish, Chinese
Video Intelligence	• N/A		
Recording Policy	Supports up to 16 channels megapixel recording (depends on product) Continuous recording Event-driven recording along with rules		

• Scheduled recording on daily or weekday basis

• Post alarm recording 1-300 seconds • Pre-alarm recording 1-300 seconds • Support individual schedule recording

Rule Manager	Conditional recording/alert/notification Email, FTP, SMS, popup window, PTZ Panel, Relay output notifications Sound, alarm, round-the-clock alerts Support email template
Remote Management	Remote operation & management via VMS Client Remote management and control via SCC & SCC Client
Remote Client	Web Client • iPhone client • Android Client
3rd Party IPCAM	ACTi, Arecont Vision, Axis, Dahua, Dynacolor, Hikvision, IQinvision, Mobotix, Panasonic, and more
Storage Expansion	Built-in RAID storage management
General & Misc.	Video privacy mask Digital zoom in, zoom out Client auto login Automatic storage recycling Client-server architecture Customized authority account management Digital watermark proofing Support DDNS function Support time synchronization with NTP server Support Customized Event management and log mechanism Auto port mapping for internet connection Support batch setting IPCAM parameters Support Health Check function Support standby recording (Failover) Support offline recording with Surveon cameras Support APC SMART-UPS
Language	Support multiple language on VMS including English, Czech, Dutch, French, German, Italian, Japanese, Korean, Persian, Polski, Portuguese, Russian, Slovak, Spanish, Turkish, Simplified Chinese, Traditional








GSe Pro 1004 Serise

Cloud NVR Series


Functions

Front View



Item	Description
1	Mute / Service button
2	Power: ON
3	Cooling: ON
4	Thermal: ON
5	System: ON

Rear View



Hardware Specifications

GSe Pro 1004-16		
System Processor	Intel Avoton 4-Core , 2.40 GHz	
System Memory	Default: DDR3 4GB	
Operating System	Linux Embedded System	
Storage	4 x 3.5" or 2.5" SATAII/SATAIII hard disk drives	
I/O Interface	• RJ-45: 4x Gigabit Ethernet • USB: 2 x USB 3.0 + 2 x USB 2.0	
RAID	0, 1 (0+1), 3, 5, 6, 10, 30, 50, 60	
Electrical	Single 250W	
Operating Environment	• Humidity: 5% to 95% (non-condensing) • Temperature: 0° to 40°C	
LED Indicator	Yes	
Dimensions	447mm (W) x 43.5mm (H) x 450mm (D)	
Weight	6.96kg / 15.34lb (without HDD)	
Certification	Safety: UL, BSMI, CB, EAC Electromagnetic Compatibility: CE, BSMI, FCC, KC	
Warranty	3 years	

Ordering Information

Model name	Description
GSe Pro 1004-4	4CH, 4-Bay Megapixel H/W RAID NVR
GSe Pro 1004-9	9CH, 4-Bay Megapixel H/W RAID NVR
GSe Pro 1004-16	16CH, 4-Bay Megapixel H/W RAID NVR
ZCDULT-0010	SCC with Unlimited Host License
ZCD5H-0010	SCC with 5 Host License
ZCD10H-0010	SCC with 10 Host License
ZCD20H-0010	SCC with 20 Host License

Optional Accessories

Part Number	Description
ZJOYSTICK-0050	CH Products, IP Desktop USB Joystick. 3 axes joysticks for P/T control, 12 HID buttons, USB 1.1 HID compliant, Easy to use and operate.
ZETHIOBOX-0030	Ethernet I/O Box, Ethernet Digital I/O Controller, Digital Input x6, Digital Output x3 (for VMS 2.4.8)
ZPOE08-0030	8 Port 10/100Mbps 120W PoE Switch
ZPOE26-0030	24 Port 10/100Mbps + 2 Port GBE Combo (UTP/ SFP) 380W PoE Switch
HUS726T4TALE6L4	Western Digital Enterprise 3.5" SATA 6Gb/s HDD, 4TB, 7200RPM
HUS726T6TALE6L4	Western Digital Enterprise 3.5" SATA 6Gb/s HDD, 6TB, 7200RPM
MG05ACA800E	Toshiba Enterprise 3.5" SATA 6Gb/s HDD, 8TB, 7200RPM

