# **GSe Pro 1008 Serise**

# **Cloud NVR Series**

- Maximum 4/9/16CH Megapixel Recording (up to 5MP or above)
- Support 8-bay Hot-Swappable SATA Hard Disk
- Enterprise Hardware RAID Function for Data Protection
- Built-in Surveon Enterprise VMS
- Scalable Client-Server Architecture

## **Software Specifications**


Live View	<ul> <li>Real-time network camera discovery</li> <li>Versatile views of various screen divisions</li> <li>Multiple views supported</li> <li>View patrolling for single or multiple views</li> <li>Real time video/event alarm monitoring</li> <li>Support 3 installation modes and 5 different fisheye dewarp display modes</li> <li>Support live audio</li> </ul>	Rule Manager	<ul> <li>Conditional recording/alert/notification</li> <li>Email, FTP, SMS, popup window, PTZ Panel, Relay output notifications</li> <li>Sound, alarm, round-the-clock alerts</li> <li>Support email template</li> </ul>
		Remote Management	Remote operation & management via VMS Client     Remote management and control via SCC & SCC     Client
eMAP	<ul> <li>Drag-n-drop camera manipulation</li> <li>Hierarchical and multiple layer map structure</li> <li>Real time event alert</li> <li>Instant live video of camera</li> </ul>	Remote Client	Web Client      IPhone client      Android Client
		3rd Party IPCAM	• ACTi, Arecont Vision, Axis, Dahua, Dynacolor, Hikvision, IQinvision, Mobotix, Panasonic, and more
PTZ	• Pan, tilt, and zoom operations (depends on camera)	Storage Expansion	Built-in RAID storage management
	<ul> <li>Built-in PTZ control panel</li> <li>Preset position (depends on camera)</li> <li>Event-driven camera patrolling</li> <li>Support OnScreen PTZ</li> </ul>	General & Misc.	<ul> <li>Video privacy mask</li> <li>Digital zoom in, zoom out</li> <li>Log viewer, log export mechanism</li> <li>Client auto login</li> <li>Automatic storage recycling</li> <li>Client-server architecture</li> <li>Customized authority account management</li> <li>Digital watermark proofing</li> <li>Support DDNS function</li> <li>Support Customized Event management and log mechanism</li> <li>Auto port mapping for internet connection</li> <li>Support batch setting IPCAM parameters</li> <li>Support standby recording (Failover)</li> <li>Support offline recording with Surveon cameras</li> <li>Support APC SMART-UPS</li> </ul>
I/O	Digital I/O management     Support Ethernet Digital I/O Controller		
Multiple Displays	<ul> <li>Support dual monitors</li> <li>Supports live view, playback, eMap functions (depends on product)</li> <li>Direct display to secondary monitor(s)</li> </ul>		
Investigation	<ul> <li>Search by date, time, and camera</li> <li>Search over multiple days</li> <li>Search over multiple cameras</li> <li>Different colored recording indicator on calendar</li> <li>Intuitive, video thumbnail search results</li> <li>Cue-in, cue-out and loop playback</li> <li>Quick playback by video thumbnails</li> <li>1/8, 1/4, 1/2, 1x, 2x, 4x, 8x play, pause, stop</li> <li>AVI-formatted video clip export</li> <li>Up to 16 channel synchronized playback (depends on product)</li> <li>Support 3 installation modes and 5 different fisheye dewarp playback display modes</li> </ul>		
		Language	Support multiple language on VMS including English, Czech, Dutch, French, German, Italian, Japanese, Korean, Persian, Polski, Portuguese, Russian, Slovak, Spanish, Turkish, Simplified Chinese, Traditional Chinese
Video Intelligence	• N/A		
Recording Policy	<ul> <li>Supports up to 16 channels megapixel recording (depends on product)</li> <li>Continuous recording</li> <li>Event-driven recording along with rules</li> <li>Scheduled recording on daily or weekday basis</li> <li>Post alarm recording 1-300 seconds</li> <li>Pre-alarm recording 1-300 seconds</li> <li>Support individual schedule recording</li> </ul>		




# **GSe Pro 1008 Serise**

#### **Functions**

#### Front View





#### **Hardware Specifications**

GSe Pro 1004-16				
System Processor	Intel Avoton 4-Core , 2.40 GHz			
System Memory	Default: DDR3 4GB			
Operating System	Linux Embedded System			
Storage	8 x 3.5" or 2.5" SATAII/SATAIII hard disk drives			
I/O Interface	• RJ-45: 4x Gigabit Ethernet • USB: 2 x USB 3.0 + 2 x USB 2.0			
RAID	0, 1 (0+1), 3, 5, 6, 10, 30, 50, 60			
Electrical	Single 250W			
Operating Environment	• Humidity: 5% to 95% (non-condensing) • Temperature: 0° to 40°C			
LED Indicator	Yes			
Dimensions	449mm(W) x 88mm(H) x 450mm(D)			
Weight	12.08kg / 26.63lbs (without HDD)			
Certification	Safety: UL, BSMI, CB, EAC Electromagnetic Compatibility: CE, BSMI, FCC, KC			
Warranty	3 years			

### Ordering Information

**Cloud NVR Series** 

Model name	Description
GSe Pro 1008-4	4CH, 8-Bay Megapixel H/W RAID NVR
GSe Pro 1008-9	9CH, 8-Bay Megapixel H/W RAID NVR
GSe Pro 1008-16	16CH, 8-Bay Megapixel H/W RAID NVR
ZCDULT-0010	SCC with Unlimited Host License
ZCD5H-0010	SCC with 5 Host License
ZCD10H-0010	SCC with 10 Host License
ZCD20H-0010	SCC with 20 Host License

## Optional Accessories

Part Number	Description
ZJOYSTICK-0050	CH Products, IP Desktop USB Joystick. 3 axes joysticks for P/T control, 12 HID buttons, USB 1.1 HID compliant, Easy to use and operate.
ZETHIOBOX-0030	Ethernet I/O Box, Ethernet Digital I/O Controller, Digital Input x6, Digital Output x3 (for VMS 2.4.8)
ZPOE08-0030	8 Port 10/100Mbps 120W PoE Switch
ZPOE26-0030	24 Port 10/100Mbps + 2 Port GBE Combo (UTP/ SFP) 380W PoE Switch
HUS726T4TALE6L4	Western Digital Enterprise 3.5" SATA 6Gb/s HDD, 4TB, 7200RPM
HUS726T6TALE6L4	Western Digital Enterprise 3.5" SATA 6Gb/s HDD, 6TB, 7200RPM
MG05ACA800E	Toshiba Enterprise 3.5" SATA 6Gb/s HDD, 8TB, 7200RPM

All specifications are subject to change without notice.
 All brand names and registered trademarks are the property of their respective owners.

